

Production Program 2025

Coated Abrasives



Art. No.	Production Width in mm	P-grit sizes																	Flexibility 1 = stiff 15 = flexible	Top Coat	Colour of product (grain-side)	Application													
		P 12	P 16	P 24	P 30	P 36	P 40	P 50	P 60	P 80	P 100	P 120	P 150	P 180	P 220	P 240	P 280	P 320					P 360	P 400	P 500	P 600	P 800	P 1000	P 1200	P 1500	P 2000	P 2500	ST3000	ST4000	ST5000
Ceramic																																			
051 XP *	1480			•																															
	1650							•	•		•																								
051 XYP *	1650				•	•																													
052 J *	1650							•	•	•	•	•	•	•	•																				
052 JF *	1650																																		
052 JFF *	1650																																		
052 XF *	1650																																		
062 XP *	1650																																		
062 XPK *	1650																																		
071 XP *	1650																																		
071 XYP *	1650																																		
Zirconia																																			
141 XP *	1650																																		
141 XYP *	1650																																		
151 XP *	1650																																		
151 XYP *	1650																																		
341 X *	1650																																		
341 XK *	1650																																		
341 XP *	1650																																		
Aluminium Oxide																																			
500 NET	1400																																		
531 J	1650																																		
531 JFF	1650																																		
541 JF	1650																																		
541 XF	1650																																		
542 JFF	1650																																		
542 JFF5	1650																																		
543 X	1650																																		
543 XK	1650																																		
552 JFF	1650																																		
562 JFF	1650																																		
641 PF	1650																																		
641 X	1650																																		
641 X, T01	1650																																		
641 XP	1650																																		
641 XYP	1650																																		
642 XF/N	1650																																		
732 X	1650																																		
Silicon Carbide																																			
942 J	1650																																		
942 JFF	1650																																		
942 JFF5	1650																																		
942 XP	1650																																		
942 XYP	1650																																		
943 X	1650																																		
981 X	1650																																		
Pearl-Grinding CP-Technology																																			
A41 XP	1650																																		
A44 X	1650																																		
A81 XP **	1650																																		
B42 XF	1650																																		
C41 XP	1650																																		
Film																																			
711 FS/NK *	1650																																		
	1650																																		
747 FS/NK *	1650																																		
	1650																																		
764 FM	1650																																		
961 FOS	1650																																		

* = no P-grits | ** = only wet grinding on heavy duty machines

STARCKE GmbH & Co. KG
Markt 10
D-49324 Melle
Phone +49 (0)5422 966-0
Telefax +49 (0)5422 966-301
info@starcke.de
www.starcke.de