

## Product Information

# 764FM

### Product structure

<b>Backing</b>	Synthetic film
<b>Flexibility</b>	low 1 ————— 5 ————— 10 high
<b>Grain Type</b>	Aluminium oxide
<b>Coating</b>	open
<b>Top Coat</b>	<input type="checkbox"/> stearate <input type="checkbox"/> special top coat
<b>Manufactured Width</b>	<input type="checkbox"/> 1400 mm <input type="checkbox"/> 1430 mm <input checked="" type="checkbox"/> 1650 mm <input type="checkbox"/> andere
<b>Form</b>	
<b>Suitable for</b>	<input checked="" type="checkbox"/> Hand sanding <input type="checkbox"/> Hand-held machine sanding <input type="checkbox"/> Machine sanding



### Grits

Ceramic, zirconia, # and \* = non P-Grits

<input type="checkbox"/> P 12	<input type="checkbox"/> P 16	<input type="checkbox"/> P 24	<input type="checkbox"/> P 30	<input type="checkbox"/> P 36	<input type="checkbox"/> P 40	<input type="checkbox"/> P 50	<input type="checkbox"/> P 60	<input type="checkbox"/> P 80	<input type="checkbox"/> P 100	<input type="checkbox"/> P 120	<input type="checkbox"/> P 150	<input type="checkbox"/> P 180	<input type="checkbox"/> P 220	<input type="checkbox"/> P 240
<input type="checkbox"/> P 280	<input type="checkbox"/> P 320	<input type="checkbox"/> P 360	<input type="checkbox"/> P 400	<input type="checkbox"/> P 500	<input checked="" type="checkbox"/> P 600	<input checked="" type="checkbox"/> P 800	<input type="checkbox"/> P 1.000	<input type="checkbox"/> P 1.200	<input type="checkbox"/> P 1.500	<input type="checkbox"/> P 2.000	<input type="checkbox"/> P 2.500	<input type="checkbox"/> ST 3.000*	<input type="checkbox"/> ST 5.000*	<input type="checkbox"/> ST 7.000*

### Materials

Aluminium	Non-ferrous metal	Stainless steel	Steel	Titanium	<b>Paint lacquer</b>	Glass	Wood	Plastics	Stone/china
-----------	-------------------	-----------------	-------	----------	----------------------	-------	------	----------	-------------

### Application examples



Automotive industry



Automotive crash repair

- Very uniform surface due to precisely coated abrasive grain
- Excellent wet sanding capability by no soaking required
- Abrasive layout purpose-made for the STARCKE MOIST SANDING SYSTEM

