


Product Information

PEARL GRINDING

A44XK

Product structure

Backing	Sturdy X-weight cotton cloth
Flexibility	low 1  5 11 high
Grain Type	Pearl Grinding - Aluminium oxide
Coating	Open
Top Coat	<input type="checkbox"/> stearate <input type="checkbox"/> special tocoat
Manufactured Width	<input type="checkbox"/> 1400 mm <input type="checkbox"/> 1430 mm <input checked="" type="checkbox"/> 1650 mm <input type="checkbox"/> other
Form	
Suitable for	<input type="checkbox"/> Hand grinding <input checked="" type="checkbox"/> Hand-held machine grinding <input type="checkbox"/> Machine grinding



Grits

Ceramic, zirconia, # and * = non P-Grits

- P 12 P 16 P 24 P 30 P 36 P 40 P 50 P 60 P 80 P 100 P 120 P 150 P 180 P 220 P 240
 P 280 P 320 P 360 P 400 P 500 P 600 P 800 P 1.000 P 1.200 P 1.500 P 2.000 P 2.500 ST 3.000* ST 5.000* ST 7.000*

Materials

- Aluminium Non-ferrous metal Stainless steel Steel Titanium Paint lacquer Glass Wood Plastics Stone/china

Application examples



Automotive industry | Body shop



Weldseam and flat rolled steel processing



Steel sheet processing

- Very long service life due to large amount of grain
- Consistent stock removal due to modified PEARL GRINDING grain bond
- Less surface roughness from start to finish thanks to the specific PEARL GRINDING grain ball structure

