

## Product Information SFS

### Product structure

**Backing** Extrem highly flexible cotton cloth backing

### Flexibility

low 1 5 11 high

**Coating** Closed coat

**Top Coat**  Stearate  Special top coat

**Maximum width of rolls**  152 mm

### Form



**Suitable for**  hand sanding  hand held machine sanding  machine sanding



### Grits

Ceramic, zirconia and \* = non P-Grits

P 12  P 16  P 24  P 30  P 36  P 40  P 50  P 60  P 80  P 100  P 120  P 150  P 180  P 220  P 240  
 P 280  P 320  P 360  P 400  P 500  P 600  P 800  P 1.000  P 1.200  ST 1.500\*  ST 2.000\*  ST 2.500\*  ST 3.000\*  ST 5.000\*  ST 7.000\*

### Materials

Aluminium Non-ferrous metal Stainless steel Steel Titanium Paint lacquer Glass Wood Plastics Stone/china

### Application examples



Tool manufacturing



Watches & Jewelry




Implants



Electronic Industry

- Extrem highly flexible cloth backing for grinding moulded workpieces to achieve a very uniform surface
- Excellent performance and even roughness by precised coated abrasive grain
- Perfect for pre-polish and finish-sanding operations



Our special expertise in the manufacture of micro grain abrasives is reflected in STARCKE's proprietary microgrit standard that is labeled with the grain code "ST". STARCKE microgrits are currently available in grain sizes ST 1.500\*, ST 2.000\*, ST 2.500\*, ST 3.000\*, ST 5.000\* and ST 7.000\*.